

UNIVERSAL ALIPHATIC POLYURETHANE TOP COAT

DESCRIPTION

MAGIECHEM 142 is a highly resistant based coating aliphatic polyurethane, can also beglossy , and also clear or colored.

MAGIECHEM 142 is used as a decorative and protective finish to surfaces exposed to weather and corrosive environments.

ADVANTAGE

- Indoor and outdoor use
- Keeps its color and luster
- Resistant to corrosive environments
- Easy to clean and maintain
- Excellent resistance to wear

APPLICATION INSTRUCTIONS

The surface must be dry and free of oil, grease, wax or any other contaminant

Concrete: Clean and dry.

For primer; MAGIECHEM5076
MAGIECHEM9461
MAGIECHEM 110

Metal: Sandblast is suggested, if not possible, use a wire brush. For the primer, use MAGIECHEM 163

Wood/Gypsum: Clean and dry. Use primer MAGIECHEM 5076 or another product on MAGIECHEMS approval

APPLICATION

- Mix parts A and B separately.
- Pour the container B into the container of part A, or in the proportions of 2 parts A and 1 part B by volume.
- Mix thoroughly for 3 minutes, and then apply.
Brush: Naturalbristles, undiluted material.
Roller: One of good quality with short bristles
Gun: Conventional or airless.
5% to 15% Solvent MAGIECHEM 242

PRECAUTIONS

- Consult MSDS before use.
- Can give a fresh epoxy coating (less than 24 hours). If not, roughen with a grinder and clean the surface with a 50/50 solution of METHYL ETHYL KETONE AND BUTYL ACETATE 50/50% of MEK & BAC and water.



MAGIECHEM



